

2007 BMW K 1200 R

MSRP: \$14,325.00*



Copyright 2006 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge.

Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Transverse mounted, liquid-cooled inline 4-cylinder	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	79 mm x 59 mm	Rear Wheel	5.50 x 17 cast alloy, five double-spoke
Displacement	1157 cc	Front Tire	120/70 x 17 tubeless
Horsepower	163 bhp @ 10250 rpm	Rear Tire	180/55 x 17 tubeless
Torque	94 lb/ft @ 8250 rpm	Dimensions	
Compression Ratio	13.0 :1	Overall Length	87.7 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	33.7 inches
Valves	2 x 32 mm mm intake / 2 x 27,5 mm mm exhaust	Wheelbase	62.2 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.7 quarts	Seat Height	32.3 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	61.0 degrees
Fuel Requirement	Unleaded, premium grade, 93 AKI	Front Wheel Trail	4.5 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	465 lbs.
Fuel Capacity	5.0 U.S. gallons including 1 gallon reserve	Weight - Wet	522 lbs.
Charging System	580 Watts @ 14 Volts	Maximum Load	992 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Standard Colors	
Cooling System	Single Radiator, 50/50 water/anti-freeze mix	Code	Price
		841	N / C
			Sun Yellow
		946	N / C
			Dark Graphite Metallic
		954	N / C
			White Aluminum Metallic
Drivetrain		Standard Equipment	
Primary Drive	1:1.559	173	\$275.00
Clutch	151 mm, multi-disc oil bath	530	\$260
1st Gear Ratio	2.52:1	519	\$235
2nd Gear Ratio	1.84:1	530	\$260
3rd Gear Ratio	1.45:1	539	\$275
4th Gear Ratio	1.28:1	560	\$210.00
5th Gear Ratio	1.14:1	588	\$50.00
6th Gear Ratio	1.01:1	603	\$235
Final Drive System	Enclosed driveshaft with two universal joints	630	\$1040.00
Final Drive Ratio	2.91:1	665	\$135.00
Frame and Suspension		774	\$N / C
Frame	Composite aluminum frame		White Turn Indicator
Front Suspension	BMW Duolever		Anti-Theft Alarm
Front Travel	4.5 inches		Integral ABS II
Rear Suspension	BMW EVO Paralever		Luggage Grid
Rear Travel	5.3 inches		Dual Bench Seat - Low (31.1 inches)
Brakes			
Brake System	BMW EVO		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single, two-piston fixed caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		