

# 2007 BMW R 1200 GS Adventure

MSRP: \$16,775.00\*



Copyright 2006 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

\*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge.

Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cross-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.00 x 17 cross-spoke
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	100 bhp @ 7000 rpm	Rear Tire	150/70 x 17 tubeless
Torque	85 lb/ft @ 5500 rpm	Dimensions	
Compression Ratio	11.0 :1	Overall Length	88.6 inches
Valve Gear	Chain-driven, high cam, OHV, w/adj. rocker arms	Overall Width	37.6 inches
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase	59.5 inches
Valves / Cylinder	Four	Ground Clearance	9.5 inches
Engine Oil Capacity	4.2 quarts	Seat Height	35.2 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	63.8 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.8 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	492 lbs. excluding options&accessories
Fuel Capacity	8.7 U.S. gallons including 1 gallon reserve	Weight - Wet	564 lbs. excluding options&accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	1025 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		751 N / C	Alpine White
Primary Drive	1:1.823	954 N / C	White Aluminum Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	Standard Equipment	
1st Gear Ratio	2.28:1	519 N / C	Heated Hand Grips
2nd Gear Ratio	1.58:1	588 N / C	Clear Turn Signal Lenses
3rd Gear Ratio	1.26:1	589 N / C	Hand Protection
4th Gear Ratio	1.03:1	771 N / C	Cross-Spoke Wheels
5th Gear Ratio	0.90:1	Available Equipment	
6th Gear Ratio	0.81:1	350 \$135	Chrome Exhaust Pipe
Final Drive System	Enclosed driveshaft with two universal joints	530 \$260	Tire Pressure Monitoring (TPM)
Final Drive Ratio	2.82:1	539 \$275	On Board Computer (incl. Oil Level Warning)
Frame and Suspension		562 \$390	Fog Lights
Frame	Three-part, engine/cast aluminum/tubular steel	603 \$235	Anti-Theft Alarm
Front Suspension	BMW Telelever	630 \$1040.00	Integral ABS II
Front Travel	8.3 inches	633 N / C	Off-Road Tires
Rear Suspension	BMW EVO Paralever	650 \$365.00	ASC
Rear Travel	8.7 inches	680 \$365	Saddle Bag Mounts for alu cases
Brakes			
Brake System	BMW EVO		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.0 inch dual floating rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		