

2007 BMW R 1200 R

MSRP: \$13,025.00*



Copyright 2006 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge.

Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	5.50 x 17 cast alloy, five double-spoke
Displacement	1170 cc	Front Tire	120/70 x 17 tubeless
Horsepower	109 bhp @ 7500 rpm	Rear Tire	180/55 x 17 tubeless
Torque	85 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	84.4 inches
Valve Gear	HC, chain-driven	Overall Width	34.3 inches
Valves	2.0 x 36.0 mm intake / 2.0 x 31.0 mm exhaust	Wheelbase	58.9 inches
Valves / Cylinder	Four	Ground Clearance	N/A
Engine Oil Capacity	4.2 quarts	Seat Height	31.5 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	62.9 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.7 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	437 lbs.
Fuel Capacity	4.6 U.S. gallons w/ approx. 1 gallon reserve	Weight - Wet	492 lbs.
Charging System	600 Watts @ 14 Volts	Maximum Load	923 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		716 N / C	Night Black
Primary Drive	1:1.882	989 N / C	Crystal Gray Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	N10 N / C	Granite Gray Metallic
1st Gear Ratio	2.28:1	Available Colors	
2nd Gear Ratio	1.58:1	730 \$250.00	Night Black with pin striping
3rd Gear Ratio	1.26:1	Standard Equipment	
4th Gear Ratio	1.03:1	Available Equipment	
5th Gear Ratio	0.90:1	350 \$135	Chrome Exhaust Pipe
6th Gear Ratio	0.81:1	416 \$800	Electronic Suspension Adjustment (ESA)
Final Drive System	Enclosed driveshaft with two universal joints	519 \$235	Heated Hand Grips
Final Drive Ratio	2.75:1	530 \$260	Tire Pressure Monitoring (TPM)
Frame and Suspension		539 \$225.00	On Board Computer
Frame	Three-part, engine/cast aluminum/tubular steel	560 \$210.00	Windshield Sport
Front Suspension	BMW Telelever	588 \$50.00	White Turn Indicator
Front Travel	4.7 inches	603 \$235	Anti-Theft Alarm
Rear Suspension	BMW Paralever	630 \$1040.00	Integral ABS II
Rear Travel	5.5 inches	636 \$120.00	Center Stand
Brakes		650 \$365.00	ASC
Brake System	BMW EVO	681 \$135.00	Saddle Bag Mounts
Front Brakes	Two, four-piston fixed calipers	774 N / C	Seat Low (30.3 inches)
Front Rotor	12.6 inch dual floating rotors	778 N / C	Seat High (32.7 inches)
Rear Brake	Single, two-piston fixed caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		