

2007 BMW R 1200 S

MSRP: \$14,725.00*



Copyright 2006 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge.

Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	5.50 x 17 cast alloy, five double-spoke
Displacement	1170 cc	Front Tire	120/70 x 17 tubeless
Horsepower	122 bhp @ 8250 rpm	Rear Tire	180/55 x 17 tubeless
Torque	83 lb/ft @ 6800 rpm	Dimensions	
Compression Ratio	12.5 :1	Overall Length	84.7 inches
Valve Gear	HC, chain-driven	Overall Width	34.2 inches
Valves	2.0 x 36.0 mm intake / 2.0 x 31.0 mm exhaust	Wheelbase	58.5 inches
Valves / Cylinder	Four	Ground Clearance	N/A
Engine Oil Capacity	4.2 quarts	Seat Height	32.7 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	66.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.4 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	419 lbs.
Fuel Capacity	4.5 U.S. gallons including 1 gallon reserve	Weight - Wet	470 lbs.
Charging System	600 Watts @ 14 Volts	Maximum Load	1014 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		716 N / C	Night Black
Primary Drive	1:1.824	954 N / C	White Aluminum Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	N03 N / C	Shine Yellow
1st Gear Ratio	2.28:1	Available Colors	
2nd Gear Ratio	1.58:1	N04 \$590.00	Titan silver metallic/magma red
3rd Gear Ratio	1.26:1	Standard Equipment	
4th Gear Ratio	1.03:1	Available Equipment	
5th Gear Ratio	0.90:1	519 \$235	Heated Hand Grips
6th Gear Ratio	0.81:1	524 \$925.00	ABS (Disconnectable)
Final Drive System	Enclosed driveshaft with two universal joints	530 \$260	Tire Pressure Monitoring (TPM)
Final Drive Ratio	2.75:1	539 \$275	On Board Computer (incl. Oil Level Warning)
Frame and Suspension		547 \$690.00	Sport Suspension "Ohlins"
Frame	Three-part, engine/cast aluminum/tubular steel	603 \$235	Anti-Theft Alarm
Front Suspension	BMW Telelever	779 \$205.00	6.0" Rear Wheel
Front Travel	4.3 inches		
Rear Suspension	BMW Paralever		
Rear Travel	4.7 inches		
Brakes			
Brake System	BMW EVO		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single, two-piston fixed caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		