

2007 BMW R 1200 ST

MSRP: \$14,925.00*

Copyright 2006 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	5.00 x 17 cast alloy, five double-spoke
Displacement	1170 cc	Front Tire	120/70 x 17 tubeless
Horsepower	110 bhp @ 7500 rpm	Rear Tire	180/55 x 17 tubeless
Torque	85 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	85.2 inches
Valve Gear	HC, chain-driven	Overall Width	35.0 inches
Valves	2.0 x 36.0 mm intake / 2.0 x 31.0 mm exhaust	Wheelbase	59.1 inches
Valves / Cylinder	Four	Ground Clearance	N/A
Engine Oil Capacity	4.2 quarts	Seat Height	31.9 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	63.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.4 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	452 lbs. excluding options & accessories
Fuel Capacity	5.5 U.S. gallons including 1 gallon reserve	Weight - Wet	505 lbs. excluding options & accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	1014 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		716 N / C	Night Black
Primary Drive	1:1.882	764 N / C	Titan Silver Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	Standard Equipment	
1st Gear Ratio	2.28:1	Available Equipment	
2nd Gear Ratio	1.58:1	350 \$135	Chrome Exhaust Pipe
3rd Gear Ratio	1.26:1	416 \$800	Electronic Suspension Adjustment (ESA)
4th Gear Ratio	1.03:1	519 \$235	Heated Hand Grips
5th Gear Ratio	0.90:1	530 \$260	Tire Pressure Monitoring (TPM)
6th Gear Ratio	0.81:1	539 \$275	On Board Computer (incl. Oil Level Warning)
Final Drive System	Enclosed driveshaft with two universal joints	603 \$235	Anti-Theft Alarm
Final Drive Ratio	2.62:1	630 \$1040.00	Integral ABS II
Frame and Suspension		636 \$120.00	Center Stand
Frame	Three-part, engine/cast aluminum/tubular steel	650 \$365.00	ASC
Front Suspension	BMW Telelever	665 \$135.00	Luggage Grid
Front Travel	4.3 inches	764 \$40.00	Accessory Socket
Rear Suspension	BMW Paralever	776 N / C	Seat - Low (30.7 inches)
Rear Travel	5.5 inches		
Brakes			
Brake System	BMW EVO		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single, two-piston fixed caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		