

2008 BMW R 1200 HP2 Sport

MSRP: \$25,375.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	3.5 x 17 forged aluminum wheel
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	6.0 x 17 forged aluminum wheel
Displacement	1170 cc	Front Tire	120/70 x 17 tubeless
Horsepower	130 bhp @ 8750 rpm	Rear Tire	190/55 x 17 tubless
Torque	85 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.5 :1	Overall Length	84.1 inches
Valve Gear	DOHC chain driven	Overall Width	29.5 inches
Valves	2 x 39 mm mm intake / 2 x 33 mm mm exhaust	Wheelbase	58.5 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	Info. Unavailable	Seat Height	32.7 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	66.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.4 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	392 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	438 lbs. excluding options & accessories
Charging System	480 Watts @ 14 Volts	Maximum Load	726 lbs. GVWR
Battery	12 Volts 12 Amps/hour	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		751 N / C	White Alpine
Primary Drive	1.734	Standard Equipment	
Clutch	180 mm dry, single plate w/ hydraulic actuation	Available Equipment	
1st Gear Ratio	2.17:1	524 \$1,000	ABS
2nd Gear Ratio	1.62:1		
3rd Gear Ratio	1.29:1		
4th Gear Ratio	1.06:1		
5th Gear Ratio	0.93:1		
6th Gear Ratio	0.84:1		
Final Drive System	Enclosed driveshaft with two universal joints		
Final Drive Ratio	2.75:1		
Frame and Suspension			
Frame	Tubular steel trellis with carbon rear subframe		
Front Suspension	BMW Telelever		
Front Travel	4.1 inches		
Rear Suspension	BMW Paralever		
Rear Travel	4.7 inches		
Brakes			
Brake System	Front and rear disc with optional ABS		
Front Brakes	Radial mounted Brembo monobloc		
Front Rotor	12.6 inch Dual Rotors		
Rear Brake	Brembo double piston floating		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		