

2008 BMW R 1200 GS

MSRP: \$14,600.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cast aluminum
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.0 x 17 cast aluminum
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	105 bhp @ 7500 rpm	Rear Tire	150/70 x 17 tubeless
Torque	85 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	87.0 inches
Valve Gear	Chain-driven, high cam, OHV, w/adj. rocker arms	Overall Width	36.6 inches
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase	59.3 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	4.2 quarts	Seat Height	33.5 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.3 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.0 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	Info. Unavailable
Fuel Capacity	5.3 U.S. gallons including 1 gallon reserve	Weight - Wet	504 lbs. excluding options & accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	968 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		764 N / C	Titan Silver Metallic
Primary Drive	1:1.737	988 N / C	Slate Gray Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	N13 N / C	Namibia Orange
1st Gear Ratio	2.38:1	N14 N / C	Tanzanite Blue
2nd Gear Ratio	1.65:1	Standard Equipment	
3rd Gear Ratio	1.30:1	Available Equipment	
4th Gear Ratio	1.07:1	350 \$PKG	Chrome Exhaust Pipe
5th Gear Ratio	0.96:1	416 \$PKG	Enduro ESA
6th Gear Ratio	0.84:1	430 \$1,650	Safety Package (530, 630, 650)
Final Drive System	Enclosed driveshaft with two universal joints	431 \$695	Equipment Package 1 (519, 539, 589, 681)
Final Drive Ratio	2.91:1	432 \$1,495	Equipment Package 2 (350, 416, 519, 539, 589, 681)
Frame and Suspension		519 \$PKG	Heated Hand Grips
Frame	Tubular steel trellis frame	530 \$PKG	Tire Pressure Monitoring (TPM)
Front Suspension	BMW Telelever	539 \$PKG	On Board Computer
Front Travel	7.5 inches	589 \$PKG	Hand Protection
Rear Suspension	BMW EVO Paralever	603 \$395.00	Anti-Theft Alarm
Rear Travel	7.9 inches	630 \$1100.00	Integral ABS II (Disconnectable)
Brakes		630 \$PKG	Integral ABS II (Disconnectable)
Brake System	BMW	650 \$PKG	ASC
Front Brakes	Two, four-piston fixed calipers	681 \$PKG	Saddle Bag Mounts
Front Rotor	12.0 inch Dual Rotors	771 \$495	Cross-Spoke Wheels
Rear Brake	Single, two-piston floating caliper	776 N / C	Low Seat (32.3 inches)
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		